

## **Light Duty Orbital Shakers**



# Choose the Perfect Light Duty Orbital Shaker You Can Trust for Reliable Everyday Shaking

Dependable OHAUS Light Duty Shakers are designed for applications with loads up to 4 kg. Choose from two orbits and speed ranges to optimize your sample mix. One digital model dedicated for use with microplates, two digital models designed to work with accessories and a non-digital economical unit for everyday shaking. All models feature triple eccentric drive systems for stable shaking with microprocessor-control for reliable shaking action.

#### **Standard Features:**

- Designed for flexibility with your applications OHAUS Light Duty Shakers include the ready-to-use tray and mat, or remove the mat and customize the tray with over 20 easyto-install accessories.
- Well-performing economical choice for your everyday laboratory shaking needs. Non-digital model offers reliable shaking across the entire speed range with the robust triple eccentric drive design.
- Microplate shaker is designed to securely hold up to four microplates or deepwell plates, or easily install two microtube racks. Units slowly increase speed to desired setpoint to avoid splashing.

# **Light Duty Orbital Shakers**

Model	SHLD0415AL	SHLD0403DG	SHLD0415DG	SHLDMP03DG
Control	Analog	Digital		
Motion	Orbital, 15 mm	Orbital, 3 mm	Orbital, 15 mm	Orbital, 3 mm
Speed Range	40 to 300 rpm	100 to 1200 rpm	40 to 300 rpm	100 to 1200 rpm
Timer	N/A	1 second to 160 hours		
Capacity		3.6 kg 4 Microplates or 2 Microtube Racks		
Working Environment	0 °C to 40 °C, 80% Relative Humidity, non-condensing	-10 °C to 60 °C, 80% Relative Humidity, non-condensing		
Drive System	Brushless DC Motor; Triple Eccentric			
Tray Size (L × W)		299 × 222 mm		279 × 197 mm
Tray Construction	Aluminum			
Dimensions ( $H \times L \times W$ )	108 × 413 × 260 mm			
Net Weight	10.9 kg			
Power	230V, 2.5A, 50/60Hz	230V, 5A, 50/60Hz		
Power Consumption	25 W			

### **Other Standard Features and Equipment**

Non-slip mat (299 × 222 mm) included with all models except SHLDMP03DG


### **Compliance**

- Product Safety: EN 61010-1, EN 61010-2-051
- Electromagnetic Compatibility: EN 61326-1 Class A, Industrial Environments
- Compliance Marks: CE; RCM; TÜV SÜD

#### Accessories

Item No.	Description	Max. per		
	Description			
30400084	Flask Clamp, 10 mL	35		
30400085	Flask Clamp, 25 mL	20		
30400086	Flask Clamp, 50 mL	15		
30400087	Flask Clamp, 125 mL	12		
30400088	Flask Clamp, 250 mL	6		
30400089	Flask Clamp, 500 mL	4		
30400097	Flask Media Bottle Clamp. 500 mL	3		
30400099	Flask Clamp PVC 125 mL	12		
30400100	Flask Clamp PVC 250 mL	6		
30400101	Flask Clamp PVC 500 mL	4		
30400114	Microtube Rack (70 tubes per rack)	2		
30400115	Tube Rack Ø 10–13 mm (63 tubes per rack)	2		
30400116	Tube Rack Ø 14–16 mm (48 tubes per rack)	2		
30400117	Tube Rack Ø 18–20 mm (35 tubes per rack)	2		
30400118	Tube Rack Ø 22–25 mm (24 tubes per rack)	2		
30400119	Tube Rack 15 mL (35 tubes per rack)	2		
30400120	Tube Rack 50 mL (12 tubes per rack)	2		
30400121	Adjustable Platform 22 × 30 cm, 2 bars	1		
30400122	Roller Bar, 22 cm (for Adjustable Platform only)	Variable		
30400123	Universal Harness	1		
30400124	Dimpled Mat, 22 × 30 cm	1		
30400125	Dilution Cup Tray	1		
Accessories for SHLD0415AL				
30400124	Dimpled Mat, 22 × 30 cm	1		
Accessories for S	HLDMP03DG			
30400114	Microtube Rack (70 tubes per rack)	2		

#### **Dimensions**



The management system governing the manufacture of this product is ISO 9001:2015 certified.



SAP Literature #

80775311\_A 20190502 © Copyright OHAUS Corporation