

### **APPLICATIONS:**

The Unisonics FXP range is a single chamber device used to clean instruments and other hardware with ultrasonic energy in a mixed water/chemical solution.

### **SPECIFICATIONS:**

Model	FXP8M	FXP8D
Timer	Mechanical (30min)	Digital (99min)
Heating Power	Nil	
Tank Material	Pressed 304 Stainless Steel	
Tank Capacity	1.7L	
Transducer Frequency	40kHz	
Ultrasonic Power	50W	
Overall Dimensions	225 x 165 x 240mm	
Internal Tank	150 x 140 x 100mm	
Gross Weight	2.5kg	
Basket	Standard: 120 x 100 x 65mm with 9mm Mesh Aperture Option: 5mm Mesh Aperture	
Lid	Standard: Stainless Steel Included Option: PVC	
Valve	Standard: No	

### **CONSTRUCTION:**

Certified by the Australian Made Campaign as Made and Owned in Australia.

Power is supplied by one single phase 10A plug.

Operating temperature should not exceed 60°C to maintain reliability and efficiency.

Minimum operating depth should not be less than 80mm.

Care should always be taken to avoid excessive spillage of solution when draining fluid.

Resin coated transducers and circuit board for moisture protection.

### **APPROVALS:**

AS/NZS 3760:2010

AS/NZS 3100:2017

Certificate of Conformity No:E990002-(C-Tick)

Certificate for inclusion of medical device – Class 1 (T.G.A.)